

WALL MOUNT/DESKTOP TEMP. HUMIDITY METER



External probe (Indoor/Outdoor)
Dual Temp. monitor
Model : 98881

Spec./ Model no.	98878	98879	98880 / 98881
Audible alarm	YES		N/A
Temp.range	-40.0~85.0°C (-40.0~185.0 °F)		-20~50°C...Air -10~50°C...Ext. Temp
Resolution	0.1°C/°F		
Accuracy	±0.6°C (-20~50°C), others ±1.2°C		±1°C
RH % range	0.1%RH~99.9%RH		20.0~90%RH
accuracy	±3%RH(at 25°C, 10~90%RH, others ±5%RH)		±5%(at 25°C), others ±7%RH
Dew Point Temp.	YES		N/A
Wet Bulb Temp.	YES		N/A
Heat Index Temp.	N/A	YES	N/A
Wet Bulb Global Temp.	N/A	YES	N/A
Power	AC Adaptor (Optional) or AAA x 4 pcs		AAAx4pcs
Operating Temp. RH	0~50°C (32~122 °F) , ,80%RH		

FEATURES :

- Wall mount / Desktop two purposes Temperature, RH% monitor and datalogger
- Jumbo size LCD display 85x56mm display Temp.RH%,date or time
- Bright red and green LEDs warns reading exceeds threshold setting or recording status.
- Dimension: 109x95x25mm (LxWxT) with a stander for desktop purposes
- High /Low alarm threshold setting function
- Audible alarm is available for model 98878.98879 only
- Maximum/Minimum : Record since powered on, recall to check
- Temperature unit: Switchable
- Optional backlight function
- Powered by AAA x 4pcs batteries
- Optional external temperature (outdoor) is available for model 98881 only

Super low cost Temperature , RH% monitor 99881 .99882(Two channels)

- Large LCD display Temp. RH% clock and date interchange in 5 seconds.
- 12hours/24 hours selectable. Every hour alarm. Maximum, Minimum display powered by battery

Supplied with :

- Meter x1 , Battery x 4(98881.98882), operation manual x 1, plain box x1(98878.79.80.81),
- Blister pack x1 (99880.99881), Battery x1(99880.99881),Manual x 1,external temperature sensor (98881.99882)



(99881)



(99882)

External probe (In/Outdoor)

	99881	99882
Temp.range	-50.0~70.0°C (-58.0~158.0 °F)	-10~50°C(Ext.Temp)
Accuracy	±1°C/1.8°F	
External Temp. (Outdoor)	N/A	YES
RH % range	20%RH~99%RH	
accuracy	±5%RH(at 25°C, 10~90%RH, others ±7%RH)	
Power	Battery 1.5V AAA x 1 pc	
Dimension	106x98x22mm	